

1. Heater System

A: SPECIFICATIONS

Item	Specifications	Condition	
Heating capacity	4.652 kW (4,000 kcal/h, 15,872 BTU/h) or more ... When 300 m ³ (10,593 cu ft)/h	<ul style="list-style-type: none"> ● Mode selector switch : HEAT 	
		<ul style="list-style-type: none"> ● Temp. control lever : FULL HOT 	
		<ul style="list-style-type: none"> ● Temperature difference between hot water and inlet air : 65°C (149°F) 	
		<ul style="list-style-type: none"> ● Hot water flow rate : 360 ℓ (95.1 US gal, 79.2 Imp gal)/h 	
Air flow rate	300 m ³ (10,593 cu ft)/h	Heat mode (FRESH), FULL HOT at 12.5 V	
Max air flow rate	510 m ³ (18,008 cu ft)/h	<ul style="list-style-type: none"> ● Temperature control lever : FULL COLD 	
		<ul style="list-style-type: none"> ● Blower fan speed : 4th position 	
		<ul style="list-style-type: none"> ● RECIRC switch position : RECIRC 	
Heater core size (height x length x width x thickness)	193.5 x 152.0 x 25.0 x 0.9 mm (7.62 x 5.98 x 0.984 x 0.035 in)	—	
Blower motor	Type	Magnet motor 230 W or less	at 12 V
	Fan type and size (diameter x width)	Sirocco fan type 150 x 75 mm (5.91 x 2.95 in)	—